# CONSIDER THIS YOUR BLAZING-FAST, ONE-BUTTON, CONFIDENCE BOOST.

Push a button. That's it. Then like lightning Whitetail LRF 600's in-view LCD display tells you the exact distance between you and serious bragging rights – from 10 to 600 yards. Powerful 4x magnification and bright, clear optics give you a breathtaking view of that big buck.

And for true horizontal distance below the line of sight, we also offer Whitetail LRF 600 models with innovative Tilt Intelligence™ technology. Efficient, compact vertical design and weather-resistant housing is tough and easy to carry. Just know you'll be hauling something much heavier on the hike home.

**801408**

## TILT INTELLIGENCE

Tilt Intelligence gives you the peace of mind you need when the opportunity arises to take the shot of a lifetime. In addition to providing the (1) line of sight distance to a target, the exclusive Tilt technology calculates the (2) true horizontal distance of the shot for more accurate aiming at a steep incline or decline.

# WHITETAIL LRF 600

801405

- 10–600 yards/meters performance.
- Powerful optical 4x magnification.
- In-view LCD display.
- Simple, one-button operation.
- Tilt Intelligence™ (801408 only).
- Includes carry case.

A-TACS
ADVANCED TACTICAL CONCEALMENT SYSTEM

801406

| Model | Range (yds.) | Magnification | Size (in. / mm) | Weight (oz. / g) | Case | Battery Type | RANGING PERFORMANCE Rflctv. (yds.) | Tree (yds.) | Deer (yds.) | Accuracy (yds.) | TILT INTELLIGENCE™ |
|---|---|---|---|---|---|---|---|---|---|---|---|
| 801405 | 10–600 | 4x | 1.9x3.6x4.2 / 50x107x103 | 7.7 / 278 | Carrying | 9-volt (not incl.) | 600 | 400 | 200 | +/– 1 | NO |
| 801405C | 10–600 | 4x | 1.9x3.6x4.2 / 50x107x103 | 7.7 / 278 | Carrying | 9-volt (not incl.) | 600 | 400 | 200 | +/– 1 | NO |
| 801406 | 10–600 | 4x | 1.9x3.6x4.2 / 50x107x103 | 7.7 / 278 | Carrying | 9-volt (not incl.) | 600 | 400 | 200 | +/– 1 | NO |
| 801406C | 10–600 | 4x | 1.9x3.6x4.2 / 50x107x103 | 7.7 / 278 | Carrying | 9-volt (not incl.) | 600 | 400 | 200 | +/– 1 | NO |
| 801408 | 10–600 | 4x | 1.9x3.6x4.2 / 50x107x103 | 7.7 / 278 | Carrying | 9-volt (not incl.) | 600 | 400 | 200 | +/– 1 | YES |
| 801408C | 10–600 | 4x | 1.9x3.6x4.2 / 50x107x103 | 7.7 / 278 | Carrying | 9-volt (not incl.) | 600 | 400 | 200 | +/– 1 | YES |